

Cable Ends

ENGINE CONTROL CABLES

Universal 3300 Cables

Application: Outboard, Inboard & Stern Drive relevant accessories.



EC-133 - Travel: 90mm | Conduit: 8.4mm | Inner: 1.9mm SS-Solid Wire | End Thread: 10-32 UNF



EC-133R - Travel: 90mm | Conduit: 8.4mm | Inner: 1.9mm SS-Solid Wire | End Thread: 10-32 UNF

BRP® - Evinrude® (OMC®) Engine Cables

Application: BRP®, Evinrude®, OMC® Engines



EC-004 (For engines manufactured Pre 1979) - Travel: 70mm | Conduit: 7.0mm | Inner: 1.9mm SS-Solid Wire

Edge Series



EEC-133 - Travel: 90mm | Conduit: 8.6mm | Inner: 2.75mm (Coated Inner) | End Thread: 10-32 UNF



EEC-014 (For OMC engines manufactured Post 1979) - Travel: 80mm | Conduit: 8.6mm | Inner: 2.7mm (Coated Inner) | Flexible core



EEC-036 (For Mercury® & Mercruiser® Engines, Mercury® Generation II series controls) - Travel: 80mm | Conduit: 8.6mm | Inner: 2.75mm (Coated Inner)



EEC-005 (For Mercury® & Mercruiser® Engines) - Travel: 95mm | Conduit: 8.6mm | Inner: 2.75mm (Coated Inner)



EEC-016 (For Mariner® engines up to 40HP) - Travel: 90mm | Conduit: 8.6mm | Inner: 2.75mm (Coated Inner) | End Thread 10/32 UNF

Stop and Fire Cables



EC-020 (Throttle / Fuel Shut Off) - Travel: 75mm | Conduit: 7.0mm | Inner: 1.9mm SS-Solid Wire



XLMRSC-LENGTH (Throttle / Fuel Shut Off) - Free Length: 175mm | Conduit: 7.0mm | Inner: 1.5mm SS-Wire Rope



XLMRFC-LENGTH (Fire Stop) - Free Length: 175mm | Conduit: 6.0mm | Inner: 1.5mm SS-Wire Rope

Disclaimer: Original part numbers and manufacturers names are mentioned for reference purposes only.